



Vitrafix VF3

Generated on 06.01.2020

Detailed description

Aluminium carrier system brackets, profiles and fixings which have been tested to BS 8414-1 and BS 8414-2 and are Centre for Window and Cladding Technology (CWCT) tested.

Designed to offer a cost effective yet strong carrier system and is suitable for all building types. The Vitrafix VF3 system has adjustability of 142–275 mm and can be further extended by combining the Vitrafix VF2 system to give an additional 26–40 mm - consult manufacturer for details.

Features and benefits:

- Lightweight.
- Durable.
- Tested to BS 8414.
- Tested to Centre for Window and Cladding Technology (CWCT).

Applications:

Uses undercut anchors to give a secret/ hidden installation of panels from 8 mm thickness and upwards.

Product guidance - As Standard

Material:

Aluminium.

Options

Fixings:

A range of fixings are available. Consult manufacturer's literature for information.

Product specification

Manufacturer

- Name: Valcan Ltd
- Web: www.valcan.co.uk
- Email: enquiries@valcan.co.uk
- Tel: +44 (0) 1278 428 245
- Address: Valcan Ltd, Unit 7 Robins Drive, Castlefields Ind. Est., Bridgwater, Somerset TA6 4DL

Product reference Vitrafix VF3

Valcan Ltd



Valcan Ltd
Valcan Ltd
Unit 7 Robins Drive
Castlefields Ind. Est.
Bridgwater
Somerset
TA6 4DL

Tel: +44 (0) 1278 428 245

www.valcan.co.uk
enquiries@valcan.co.uk



Brackets	VF100DB - 100 mm double bracket (no pad), 102–132 mm adjustment. VF100SB - 100 mm single bracket (no pad), 102–132 mm adjustment. VF140DB - 140 mm double bracket (no pad), 142–172 mm adjustment. VF140SB - 140 mm single bracket (no pad), 142–172 mm adjustment. VF180DB - 180 mm double bracket (no pad), 182–212 mm adjustment. VF180SB - 180 mm single bracket (no pad), 182–212 mm adjustment. VF200DB - 200 mm double bracket (no pad), 202–232 mm adjustment. VF200SB - 200 mm single bracket (no pad), 202–232 mm adjustment.
Rails	VFTR503 - T Rail, 50 x 100 x 3000 mm. VFTR506 - T Rail, 50 x 100 x 6000 mm. VFLR503 - L Rail, 50 x 50 x 3000 mm. VFLR506 - L Rail, 50 x 50 x 6000 mm.
Horizontal Rails	VFSFR3 - Horizontal Secret Fix Rail, 3000 mm. VFSFR6 - Horizontal Secret Fix Rail, 6000 mm.
Secret Fix Brackets	VFSKFX - Secret fix bracket for Keil fixing - fixed/adjustable bracket VFSKFL - Secret fix bracket for Keil fixing - floating bracket
Fixings	[]
Accessories	[None] [VFTPDB] - Double bracket thermal pad, adds 3 mm adjustment. [VFTPSB] - Single bracket thermal pad, adds 3 mm adjustment.