



The Defining Standard

DECLARATION OF PERFORMANCE

No: DoP/CPA1/UKCA/Rev1/7.2023

Product Name / Code:		Ceramapanel A	Ceramapanel A1		
Intended Use:		Fibre Cement Flat Sheets Type NT For Internal and External			
		Walls and ceilings. Category A Class 3			
Manufacturer:		Fairview Europe, Dunball House, Woodlands Court Business			
		Park, Bridgwater, TA6 4FJ, Somerset UK.			
Authorised Representative:		N/A			
AVCP System 4			Initial Type Testing (ITT) and Factory Production Control (FPC) is		
		conducted by the manufacturer			
Designated Standard:		BS EN 12467:2012+A2:2018			
Approved Body:		N/A			
FPC Certificate:		Not applicable			
		Declared pe	erformance		
Essential characteristics		Performance Designated techi specification		Designated technical	
				specification	
				BS EN 12467:2012+A2:2018	
Dimensions:	Level 1			-	
Density:	1627 Kg/m ³				
20					
Water Impermeability:	Pass				
water impermeability.					
Soak Dry:	R _L ≥ 0.75				
Suak Diy.					
Warm Water Soak:	R _L ≥ 0.75				
vvarm vvater Soak.	RL 2 0.73				
Heat/Dain Incorporating	Pass				
Heat/Rain Incorporating Pass Thermal Shock:					
Reaction to Fire:	A1				
Freeze Thaw:	R∟≥ 0.75				
Bending Strength - MOR:	Mean: 19.857 MPa				
	Minimum Wet: 13.931 MPa (Class 3)				
	William vvet. 13.931 WFa (Class 3)				
Dangerous substances:	NPD				
			-/		

The performance of the product identified above, is in conformity with the declared performances in the table above. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Simon Tennent (Managing Director)

UK 19-07-2023